

Product Name	Driveway paint
Product reference	PP94
Product description	Water borne acrylic coating for the decoration and refurbishment of tarmac and concrete paths and driveways. Driveway paint produces a tough, water and oil resistant coating which enhances the appearance of coated surfaces.
Uses	Decoration and refurbishment of tarmac and concrete driveways
Pack sizes availability	5, 10 litres
Colour range	Black, red, green
Specific gravity	Approx 1.3
Flash point	Non flammable
Recommended Spreading rate	2-3 m <sup>2</sup> /litre
Solids content	Approx 55% w/w Approx 40% v/v
Drying time	Approx 2-4 hours 20°C 65%RH
Over-coating time	Approx 6-8 hours 20°C 65%RH Allow minimum 24 hours before parking cars on coated surfaces
Minimum application temperature	Air and surface temperature should be 5°C and rising. Do not apply during damp or frosty weather or when rain is imminent
Recommended dry film thickness	Approximately 160microns
Method of application	Brush, roller or airless spray
Preparation	Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice. Treat organic growth with fungicidal solution and apply a proprietary weed killer to plant growth.
Storage life	Min 12 months in original sealed containers. Protect from frost and direct heat
Thinning/cleaning	Thin where necessary with clean water. Do not exceed 1 part water to 10 parts of Driveway Paint. Wash equipment immediately after use with water and detergent
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	Limit for this product Cat A/i 140g/l (2010). This product contains maximum 10g/l VOC
Disposal	As supplied or containing liquid product – non hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11 Used containers drained/rigorously scraped out and containing only dry residues: categorised as non-hazardous with waste code 15 01 02 (plastic package) and 15 01 04 (metal package)