

TECHNICAL DATA SHEET

TDS: CVV60715C

UNIVERSAL DEGREASER / CLEANER

100/V607/15

DESCRIPTION:

A careful blend of solvents to give powerful cleaning and degreasing properties.

RECOMMENDED USE:

To be used to degrease and remove oil patches etc from floors, walls, interior and exterior surfaces prior to acid etching or painting. Part of the cleaning process. Essential for a good finish. Can also be used as a general degreaser on metals.

AVAILABILITY:

2.5 litre

FINISH:

N/A

COLOUR:

Clear thin liquid.

TYPICAL S.G. (SPECIFIC GRAVITY):

0.86 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

41 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application restrictions N/A

Method: N/A

Thinner (Max vol): N/A

Nozzle size:

Nozzle pressure: N/A

Cleaning solvent: N/A

Recoat interval: N/A

SURFACE PREPARATION:

Clear and sweep the area to be degreased to remove debris.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-VAR

Email: info@coo-var.co.uk

www.coo-var.co.uk

UNIVERSAL DEGREASER / CLEANER**100/V607/15**

MIXING INSTRUCTIONS:

N/A

APPLICATION CONDITIONS:

Ensure adequate ventilation.

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

Suitable Coo-Var primer / top coat as required.

REMARKS:

Flamability limits in air:- Lower - 0.6% by volume
Upper - 7% by volume Vapour pressure:-
2.9mm HG @ 20°C

HEALTH AND SAFETY:

See safety data sheet - SDS 10700

ISSUED:

18 September 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var

Email: info@coo-var.co.ukwww.coo-var.co.uk